

NTM2

→ 简介

(RTD) (TC)
4mA~20mA

U_i: 28V I_i: 93mA P_i: 670mW C_i: 0μF L_i: 0mH

:
-40°C ~ +85°C
10%RH ~ 90%RH(40°C)
80kPa ~ 106kPa
-40°C ~ +85°C

→ 技术参数

: Ex ia IIC T4/T6 Ga
T4: -40°C ~ +60°C
T6: -40°C ~ +50°C
: 12V DC ~ 28V DC
:
: K, E, S, B, J, T, R, N WRe3-WRe25
WRe5-WRe26
: Pt100 Cu100 Cu50 BA1 BA2
:
: 4mA~20mA
:
 $R_t \leq [(U-12)/0.022]\Omega$ U
(25°C ± 2°C):

→ 型号命名规则

→ 接线图


K/E/J/N/T	<300°C	±0.3°C
	≥300°C	±0.1% F.S
S/B/R/WRe-	<500°C	±0.5°C
	≥500°C	±0.1% F.S
Pt100/Cu100/Cu50 /BA1/BA2	<100°C	±0.1°C
	≥100°C	±0.1% F.S

: ≤1s
: 50ppm/°C
: ±1°C(10
: -40°C~+85°C
: EMC IEC 61326-3-1
mA , () :
≥1500 V AC(/)
: ≥100MΩ(/)

3, 4, 5, 6

U_o: 5.9V I_o: 24mA P_o: 36mW C_o: 40μF L_o: 40mH

1, 2



Nanjing New Power Electric Co., Ltd.

1.2N.m



→ 补充说明



M3

0.5N.m



0.2mm²~2.5mm²

→ 组态



→ 典型安装

- 1.
- 2.
- 3.
- 4.
- 5.
- 6.
- 7.

→ 注意事项

IP 20

)

IEC/EN 60664-1

2